TITLE OF THE INVENTION

METHOD AND APPARATUS OF OPTIMALLY DESIGNING A STRUCTURE

5 ## FIELD OF THE INVENTION

The present invention relates to a method of optimally designing a structure through a solution of design parameter optimization problem and its apparatus, and more particularly, to an automatic designing

10 technique for shape optimization including a structural member topology.

BACKGROUND OF THE INVENTION

Optimal designing of structural topology is a

15 problem to determine an optimal topology and shape size of structural members under a given condition. Hereinbelow, the structural member topology and shape size will be referred to as "design argument functions", and the above decision problem will be referred to as a

20 "design argument function optimization problem". The term "argument function" is used since the topology and shape size are three-dimensional functions. In a design argument function optimization problem, an optimization problem of status argument function must

25 be solved for values of each design argument function. From this meaning, the structural topology optimal designing can be regarded as a dual structure

optimization problem having a status argument function

optimization problem inside and a design argument

function optimization problem outside.

In the inner status argument function

5   optimization problem, the concept, based on accumulated

technologies of dividing space into a finite number of

elements is employed. Particularly in a problem with

strain energy of structural member as an evaluation

functional, a finite element method is generally

10   applied as an analysis method. As a solution of finite

element method, a direct method to linear equation is

employed.

On the other hand, as to the design argument

function optimization problem, briefly the following 3

15   types of methods are provided (See non-patent document

1 or 2).

1. Evolutionary method (hereinbelow, "E method")

2. Homogenization method (hereinbelow, "H method")

3. Material distribution method (hereinbelow, "MD

20   method) or Density method (hereinbelow, "D method")

In the E method, each of subspace obtained by

space division is called a cell, and generation and

deletion of cell is repeated in accordance with an

appropriate rule. The structural members are given as

25   a set of finally existing cells. As only two status,

whether a cell exists or not, are permitted, clear

structural members can be obtained. Further, as

2

differential information of evaluation functional is
not used, there is no trap in local optimal solution.
Accordingly, the method is effective in a case where
the evaluation functional is polymodal. In patent

5   document 1, provided is a framed structural member
optimization designing apparatus using a genetic search
method which is a kind of the E method. The problem of
conventional technical art, which has required trial
computation based on accumulated know-how and which

10 cannot be applied to an actual designing problem having
a large number of design variables, is solved by the
optimization designing apparatus, by the following
arrangement. That is, an approximation optimization
computer using an approximation equation for discrete

15 design variable data such as frame member cross-
sectional size, and a detailed optimization computer
using the design variable data are provided, and these
two computers are combined to a framed structural
member optimization designing apparatus.

20   The H method enables use of sensitivity analysis
by assuming a further fine structure as structural
elements positioned in divided respective areas and
introducing a design argument function taking a
continuous value. The sensitivity analysis is an

25 analysis method utilizing differential information of
evaluation functional for a design argument function.
If the sensitivity analysis is possible, an iterative

solution such as a gradient method can be used. In comparison with a round-robin method such as the E method, at least computation time of search related to local optimal solution can be greatly reduced (See non-

5   patent document 3).

The MD method or the D method represents changes in topology and shape size of structural members by allocating real numbers ranging from 0 to 1 indicating the rate of existence to respective structural members.

10   These methods are similar to the H method in that the sensitivity analysis is enabled by replacing the discrete information as to whether or not a structural member exists with a continuous value of the rate of existence. However, as the number of parameters is

15   smaller than that in the H method, the MD and the D method can be easily modeled and has a wide range of application.

The non-patent document 4 discloses a structure phase optimization method by the D method. The method

20   has the following features. As a voxel finite element method (division of space at equal intervals) is employed, an element stiffness matrix is the same for every element. Accordingly, once the element stiffness matrix is computed, it can be used in subsequent

25   computation. Further, as the elements are regularly arranged, it is not necessary to store nodal number information of the respective elements. As a conjugate

4

gradient method with preconditioning and an element-by-element method are combined to solve a large scale simultaneous linear equations, a solution can be obtained without formation of global stiffness matrix.

5   Thus the necessary memory capacity is small.

In the homogenization method, 6 design variables (in the case of three dimensional structure) are required for 1 element. Further, the element stiffness matrix must be re-calculated upon each change of design

10   variable. On the other hand, if the density method to represent the rate of existence of structural number as a density ratio is employed, the number of design variables to 1 element is 1. In addition, the change of design variable does not influence the element

15   stiffness matrix.

[Patent Document 1]

Japanese Patent Application Laid-open No. 11-314631

[Non-patent Document 1]

20   S. Bulman, J. Sienz and E. Hinton: "Comparisons between algorithms for structural topology optimization using a series of benchmark studies", Computers and Structures, 79, pp. 1203-1218 (2001)

[Non-patent Document 2]

25   Y-L. Hsu, M-S. Hsu and C-T. Chen: "Interpreting results from topology optimization using density contours", Computers and Structures, 79, pp. 1049-1058

(2001)

[Non-patent Document 3]

· Hiroshi Yamakawa: "Optimization design",
Computational Mechanics and CAE series 9, Baifu-kan
5 (1996)

[Non-patent Document 4]

Fujii, Suzuki and Ohtsubo: "Structure phase
optimization using boxel finite element method",
Transactions of JSCES, Paper No. 20000010 (2000).

10 However, the above conventional techniques have
the following drawbacks.

Generally, a structure optimization problem is
formulated as a dual optimization problem including a
status variable vector optimization problem at each
15 repetitive step of design variable vector optimization
problem. Assuming that the design variable vector
optimization problem is referred to as an external
optimization and the status variable vector
optimization problem is referred to as an internal
20 optimization, the internal optimization is a problem to
obtain a status variable vector with a design variable
vector as a parameter, i.e., the design variable vector
being fixed. This problem is generally called
structural analysis, which can be solved by using
25 solution of linear equation with a finite element
method.

However, if the structure has changed and a

structural member in an area does not exist, e.g., a hole is formed in a member, the design variable corresponding to the element becomes 0. As a result, the Young's modulus of the element becomes 0. Then the

5   coefficient matrix of the linear equation is not full-ranked, and the problem cannot be solved by a direct method since an inverse matrix cannot be calculated.

In the conventional art, when a design variable vector becomes 0, the following countermeasures are

10   taken.

The equations are re-formed such that the coefficient matrix becomes full-ranked, i.e., the number of ranks and that of equations are equal.

Otherwise, the value of the design variable

15   vector is replaced with a small value approximate to 0.

However, in the former method, as the equations may be updated upon each update of the design variable vector, it takes much computation time.

Further, in the latter method, setting the

20   element design variable to a small value means that a physically thin film or a weak member exists. That is, in the conventional art, as a portion where material does not exist cannot be accurately represented, there is some doubt in the accuracy of obtained computation

25   result.

SUMMARY OF THE INVENTION

7

The present invention has been made in consideration of the above drawbacks of the conventional art, and provides a structure optimal designing method and its apparatus for execution of

5 computation without particular processing even when a global stiffness matrix becomes singular, thereby simplify a program and further reduce the amount of computation.

According to the present invention, provided is a

10 method of optimally designing a structure comprising a step of obtaining a solution of a structure optimal designing problem, formulated as a dual optimization problem having a first solution process to solve an optimization problem of a first evaluation functional

15 for a status variable vector and a design variable vector and a second solution process to solve an optimization problem of a second evaluation functional for the status variable vector and the design variable vector. When the status variable vector is a

20 displacement in each node, and the design variable vector is an existence ratio of a structural member in each element, the first solution process includes the second solution process as one step, and further includes a design variable update step of reading the

25 design variable vector and the status variable vector stored in a first storage unit, updating the design variable vector, and storing the updated design

8

variable vector into the first storage unit, and the

second solution process includes a status variable

update step of reading the design variable vector and

the status variable vector stored in a second storage

5   unit, updating the status variable vector, and storing

the updated status variable vector into the second

storage unit. The second evaluation function at the

second solution process comprises a norm of residual

vector, and the status variable vector is not

10   initialized upon start of the second solution process.

Note that at the second solution process, any one

of a conjugate residual method, a GCR method, a GCR(k)

method, an Orthomin(k) method, a GMRES(k) method and

their derivative methods is executed. Further, at the

15   second solution process, any one of a conjugate

residual method, a GCR method, a GCR(k) method, an

Orthomin(k) method, a GMRES(k) method and their

derivative methods is executed.

Further, according to the present invention,

20   provided is a method of optimally designing a structure

comprising a step of obtaining a solution of a

structure optimal designing problem, formulated as a

dual optimization problem having a first solution

process to solve an optimization problem of a first

25   evaluation functional for a status variable vector and

a design variable vector and a second solution process

to solve an optimization problem of a second evaluation

9

functional for the status variable vector and the

design variable vector. When the status variable

vector is a displacement in each node, and the design

variable vector is an existence ratio of a structural

5   member in each element, the first solution process

including the second solution process as one step, and

further including a design variable update step of

reading the design variable vector and the status

variable vector stored in a first storage unit,

10   updating the design variable vector, and storing the

updated design variable vector into the first storage

unit, and the second solution process comprising a

conjugate gradient method, and including a

preconditioning step of executing preconditioning on a

15   nodal force vector based on a global stiffness matrix,

and a status variable update step of reading the design

variable vector and the status variable vector stored

in a second storage unit, updating the status variable

vector, and storing the updated status variable vector

20   into the second storage unit. The status variable

vector is not initialized upon start of the second

solution process.

     Note that at the first solution process, any one

of a sequential linear programming method, an

25   optimality criteria method, and a sequential convex

function approximate method is performed. Further, at

the preconditioning step, a component in a row or

10

column of the nodal force vector is set to 0 when a diagonal component in the corresponding row or column of the global stiffness matrix becomes 0.

5   According to the present invention, further provided is an apparatus performing the above mentioned methods and a program to be executed by the apparatus performing the above mentioned methods.

In accordance with the present invention as described above, even if a global stiffness matrix

10   becomes singular, computation can be executed without particular processing, thereby a program can be simplified, and further, the amount of computation can be reduced.

Other features and advantages of the present

15   invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same name or similar parts throughout the figures thereof.

20

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together

25   with the description, serve to explain the principles of the invention.

Fig. 1 is a block diagram showing the

11

construction of a structure optimal designing apparatus according to an embodiment of the present invention;

Fig. 2 shows structures of primary storage device and secondary storage device in Fig. 1;

5   Fig. 3 is a flowchart showing a processing procedure according to the embodiment;

Fig. 4 is a flowchart showing an example of processing at step S105 in Fig. 3 in detail;

Fig. 5 is a flowchart showing another example of

10   the processing at step S105 in Fig. 3 in detail;

Fig. 6 is an explanatory diagram of setting of particular problem according to the embodiment; and

Fig. 7 is an explanatory diagram of the result of computation of the problem in Fig. 6 according to the

15   embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described in detail in accordance with the

20   accompanying drawings.

Hereinbelow, the construction and operation of a structure optimal designing apparatus to realize a structure optimal designing method according to the present invention will be described.

25   <Construction of Structure Optimal Designing Apparatus>

Fig. 1 shows the construction of the structure optimal designing apparatus according to an embodiment

of the present invention.

In Fig. 1, reference numeral 201 denotes a CPU for computation and control; 202, a display unit; 203, an input unit; 204, a primary storage unit; 205, a

5   secondary storage unit, 206, a communication unit; and 207, a bus line. Note that constituent elements in the present embodiment are stored, as programs, in the secondary storage unit 205 in advance, loaded into the primary storage unit by command input from the input

10   unit 203 or the communication unit 206, and executed by the CPU 201.

Fig. 2 shows data and programs stored in the primary storage unit 204 and the secondary storage unit 205 to realize the structure optimal designing method

15   according to the present embodiment.

The primary storage unit 204 comprising a RAM or ROM has a data storage area 214 and a program storage area 224. In Fig. 2, the unchanged and resident OS and BIOS programs and unchanged parameters for the OS and

20   BIOS are not shown. Various data to realize the structure optimal designing of the present embodiment are temporarily stored in the data storage area 214. Among these data, re-used/repetitively-used data must be temporarily stored. Data not requiring storage are

25   not necessarily temporarily stored.

For example, the data storage area 214 holds x (status variable vector) 214a, f (design variable

13

vector) 214b, L_1 (status variable vector evaluation

function) 214c, L_2 (design variable vector evaluation

function) 214d, B_1 (status variable boundary condition)

214e, W_0 (design variable weight condition) 214f, $X^{(0)}$

5   or $f^{(0)}$ (initial value) 214g, λ (Lagrange undetermined

constant) 218h, A (element stiffness matrix) 214i, k

(number of repetitive design variable changes) 214j, C

(sensitivity coefficient) 214k, r (residual vector)

214m, p (search direction vector) 214n, $r^{(0)}$ or $p^{(0)}$

10   (initial value) 214p, t (number of repetitive status

variable changes) 214q, b (nodal force vector) 214r,

and other data 214s. On the other hand, programs

loaded from the secondary storage unit 205 or the

communication unit 206 are stored in the program

15   storage area 224 and executed by the CPU 201.

Preferably, the secondary storage unit 205 is an

external large capacity memory and more preferably is a

removable memory such as a floppy disk or a CD. The

secondary storage unit 205 also has a data storage area

20   215 and a program storage area 225.

In the data storage area 215, although not shown

in detail, various initial values 215a, various

conditions 215b and a dual optimal solution problem

database 215c are stored. Further, a standardized

25   matrix or the like may be stored as the database 215c.

The program storage area 225 holds, an optimality

criteria module 225a, a sequential convex function

14

approximation module 225b, a sequential linear

programming module 225c, and other method modules 225d,

which are used as solutions in design variable vector,

and a conjugate residual module 225e, a GCR module 225f,

5   a GCR(k) module 225g, an Orthomin(k) module 225h, a

GMREG(k) module 225i, and other method modules 225j,

which are used as solutions in status variable vector.

A module corresponding to a method selected from the

programs stored in the program storage area 225 is

10   loaded into the program storage area 224 of the primary

storage unit 204 and executed by the CPU 201, thereby

the structure optimal designing method of the present

embodiment is realized.

Note that the conjugate residual module 225e may

15   be a conjugate gradient module shown in another example.

Further, it may be arranged such that both of the

conjugate residual module and the conjugate gradient

module are held and selectively used.

That is, the structure optimal designing

20   apparatus having a first solution module to solve an

optimization problem of a first evaluation functional

for a status variable vector and a design variable

vector and a second solution module to solve an

optimization problem of a second evaluation functional

25   for said status variable vector and said design

variable vector, for obtaining a solution of a

structure optimal designing problem, formulated as a

dual optimization problem, wherein said status variable

vector is a displacement in each node, said design

variable vector is an existence ratio of a structural

member in each element, and said second evaluation

5   function at said second solution module comprises a

norm of residual vector, and said status variable

vector is not initialized upon start of said second

solution module. At said first solution module, any

one of a sequential linear programming method, an

10   optimality criteria method, and a sequential convex

function approximate method is executed. At said

second solution process, any one of a conjugate

residual method, a GCR method, a GCR(k) method, an

Orthomin(k) method, a GMRES(k) method and their

15   derivative methods is executed.

Further, the structure optimal designing

apparatus having a first solution module to solve an

optimization problem of a first evaluation functional

for a status variable vector and a design variable

20   vector and a second solution module to solve an

optimization problem of a second evaluation functional

for said status variable vector and said design

variable vector, for obtaining a solution of a

structure optimal designing problem, formulated as a

25   dual optimization problem, wherein said status variable

vector is a displacement in each node, said design

variable vector is an existence ratio of a structural

member in each element, said second solution module comprising a conjugate gradient method and including a preconditioning means for executing preconditioning on a nodal force vector based on a global stiffness matrix,

5 and said status variable vector is not initialized upon start of said second solution process. At said preconditioning means, a component in a row or column of the nodal force vector is set to 0 when a diagonal component in the corresponding row or column of the

10 global stiffness matrix becomes 0. At said first solution module, any one of a sequential linear programming method, an optimality criteria method, and a sequential convex function approximate method is performed.

15 <Formulation of Structure Optimization Problem>

For the following description, a structure optimization problem is formulated.

Assuming that argument functions are represented as finite dimensional vectors by finite element

20 formulation, the argument function evaluation functional becomes a variable vector evaluation function. Hereinbelow, descriptions will be made based on the above assumption.

The status variable vector x and the design

25 variable vector f are represented as follows as matrix vectors.

$$x = (x_1, x_2, \ldots, x_m)^T \quad \ldots(1)$$

17

$$f = (f_1, f_2, \ldots, f_n)^T \quad \ldots(2)$$

In the expressions, "T" means transposition. "x" is an m-dimensional vector, and "f", an n-dimensional vector. In a structure optimization problem, a status

5 variable vector is formed with displacement of node, and a design variable vector is formed with the rate of existence of structural member in each element.

For example, in a structure optimization problem in a two-dimensional plane, if a design area is divided

10 in vertical n_y and lateral n_x elements,

As the number of elements n, $(n_x \times n_y)$ holds, and as the number of nodes, $(n_x+1) \times (n_y+1)$ holds.

As the status variable vector is represented as a pair of vertical displacement and lateral displacement

15 of each node, as the dimension m of the status variable vector x, $2 \times (n_x+1) \times (n_y+1)$ holds.

The boundary condition for x is normally given as a displacement constraint condition. The condition is described as B_1.

20 $$B_1(x) = 0 \quad \ldots(3)$$

The evaluation functions for the status variable vector x and the design variable vector f, L_1 and L_2, are defined as follows.

$$L_1 := L_1(x,f) = (b-Ax)^T(b-Ax) \quad \ldots(4)$$

25 $$L_2 := L_2(f,x) = (1/2)x^T Ax \quad \ldots(5)$$

Note that "A" is a global stiffness matrix, and "b" is a nodal force vector. The vector b is

18

previously given. The matrix A is a function of the design variable vector f.

The global stiffness matrix can be formed by superposition of element stiffness matrix A_j over an

5 element j. In the case of plane strain problem, the element stiffness matrix in consideration of the design variable vector i.e. the rate of existence f_j of structure element is as follows. Note that 4 node elements are employed as two-dimensional elements and

10 the element displacement vector x_j is made as follows.

$$X_j = (u_1, v_1, u_2, v_2, \ldots, u_4, v_4) \quad \ldots (6)$$

"u_k" and "v_k" are horizontal displacement and lateral displacement of a node k.

The element stiffness matrix corresponding to the

15 element displacement vector in the expression (6) is represented as follows.

$$A_j = f_j^{\xi} \begin{bmatrix} a_{1,1} & b_{1,1} & a_{1,2} & b_{1,2} & a_{1,3} & b_{1,3} & a_{1,4} & b_{1,4} \\ c_{1,1} & d_{1,1} & c_{1,2} & d_{1,2} & c_{1,3} & d_{1,3} & c_{1,4} & d_{1,4} \\ a_{2,1} & b_{2,1} & a_{2,2} & b_{2,2} & a_{2,3} & b_{2,3} & a_{2,4} & b_{2,4} \\ c_{2,1} & d_{2,1} & c_{2,2} & d_{2,2} & c_{2,3} & d_{2,3} & c_{2,4} & d_{2,4} \\ a_{3,1} & b_{3,1} & a_{3,2} & b_{3,2} & a_{3,3} & b_{3,3} & a_{3,4} & b_{3,4} \\ c_{3,1} & d_{3,1} & c_{3,2} & d_{3,2} & c_{3,3} & d_{3,3} & c_{3,4} & d_{3,4} \\ a_{4,1} & b_{4,1} & a_{4,2} & b_{4,2} & a_{4,3} & b_{4,3} & a_{4,4} & b_{4,4} \\ c_{4,1} & d_{4,1} & c_{4,2} & d_{4,2} & c_{4,3} & d_{4,3} & c_{4,4} & d_{4,4} \end{bmatrix} \quad \ldots (7)$$

20

In the expression,

$$a_{i,j} = (\lambda + 2\mu) \langle \partial_x e_i, \partial_x e_j \rangle + \mu \langle \partial_y e_i, \partial_y e_j \rangle \quad \ldots (8)$$

25 $$b_{i,j} = \lambda \langle \partial_x e_i, \partial_y e_j \rangle + \mu \langle \partial_x e_j, \partial_y e_i \rangle \quad \ldots (9)$$

$$c_{i,j} = \lambda \langle \partial_x e_j, \partial_x e_i \rangle + \mu \langle \partial_x e_i, \partial_y e_j \rangle \quad \ldots (10)$$

$$d_{i,j} = (\lambda + 2\mu)\langle \partial_y e_i, \partial_y e_j \rangle + \mu\langle \partial_x e_i, \partial_x e_j \rangle \quad \ldots(11)$$

"e_j" is a basic vector to a node j, and angle brackets $\langle \ , \ \rangle$ represent a vector inner product. "∂_x" is a partial differential for x, and "∂_y", a partial differential for y. The value of "ξ", in accordance with the above-described (non-patent document 4), is 2. further, "λ" and "μ" are material constants, which are referred to as Lame's constants, calculated from Young's modulus E and Poisson ratio ν as follows.

$$\lambda = E\nu/(1+\nu)(1-2\nu) \quad \ldots(12)$$

$$\mu = E/\{2(1+\nu)\} \quad \ldots(13)$$

As it is easily understood from the expression (7), if the rate of existence of an element is 0, all the components of the element stiffness matrix A_j are 0. As the global stiffness matrix is formed by superposition of element stiffness matrix, if the design variable f_j of element including the node j is 0, all the components of row and column corresponding to the node j of the global stiffness matrix are 0. In this manner, the global stiffness matrix in the structure optimization problem is generally a singular matrix.

The constraint condition for the design variable in the case of structure optimal designing is an upper limit value W_0 of total weight.

$$W(f) = \sum_{j=1}^{j=n} f_i \leq W_0 \quad \ldots(14)$$

Further, the constraint condition for the range of value of the design variable is as follows.

$$0 \leq f_j \leq 1 \quad j = 1, \ldots, n \quad \ldots(15)$$

From the above expressions, the optimal designing problems is formulated as a problem to minimize the expression (5) under the constraint conditions (14) and (15).

Further, the status variable x can be obtained as a solution to minimize the expression (4) under the constraint condition (3).

<Operation of Structure Optimal Designing Apparatus>

Next, a processing procedure according to the present embodiment will be described based on the above formulation.

Fig. 3 is a flowchart showing the processing procedure according to the embodiment.

In Fig. 3, at step S101, data in a system to be simulated is read, and variable initialization is performed. As the data reading, input data may be read from the input unit 203 or the communication unit 206, or data previously stored in the secondary storage unit 205 as a file, may be read. The data of the system includes the x and f initial values $x^{(0)}$ and $f^{(0)}$, the boundary condition B, and the evaluation functions L_1 and L_2. The program ensures a necessary variable areas in the primary storage unit 204 based on the information, and set values. A sensitivity coefficient

21

initial value $C_j^{(0)}$ is calculated by

$$C_j^{(0)} = -(x_j^{(0)})^T(\xi(f_j^{(0)})^{\xi-1}A_j)x_j^{(0)} \quad ...(16)$$

At step S102, the number of repetitions k is initialized to 1. The number of repetitions k

5   indicates repetitive processing on the above-described design variable solution process. The repetitive processing is terminated when a predetermined termination condition (conditions of evaluation functions L_1 and L_2) is satisfied.

10   At step S103, the Lagrange's undetermined constant λ is updated. At step S104, the design variable vector f is updated. At step S105, the status variable vector x is updated. At step S106, the sensitivity coefficient is calculated.

15   The above-described steps S103 and S104 differ in accordance with method employed as a solution of constraint-conditioned optimization problem. For example, the solution step of calculating the design variable vector $f^{(k)}$ is realized by one of a sequential

20   linear programming, an optimality criteria method, and a sequential convex function approximate method. Hereinbelow, the case of optimality criteria method and the case of sequential convex function approximate method as the solution will be described.

25   (Optimality Criteria Method)

First, the case where the optimality criteria method will be described. An optimality criteria

method for a structure optimization problem is well

known as disclosed in the (non-patent document 4), the

(non-patent document 5) and the like.

In the optimality criteria method, the

5 expressions (4) and (5) are combined into one

expression by using the Lagrange's undetermined

constant λ.

$$L(f,\lambda) = L_2(f,x) - \lambda(W(f)-W_0) \quad ...(17)$$

The updating of the Lagrange undetermined

10 constant λ at step S103 is made by using the following

expression.

$$\lambda^{(k+1)} = \min[0,[(1/W_0)W(f^{(k)})]^{\alpha}\lambda^{(k)}] \quad ...(18)$$

Note that the superscripts "k" and "k+1"

represent the number of repetitions. Further, "α" is a

15 power coefficient generally set to about 0.85.

The updating of the design variable at step S104

is made by the following expression.

$$f_j^{(k)} = \max[(1-\zeta)f_j^{(k-1)},0] \quad \text{if } s_j^{(k-1)} \leq \max[(1-\zeta)f_j^{(k-1)},0]$$

20 $$= \min[(1+\zeta)f_j^{(k-1)},1] \quad \text{if } \min[(1+\zeta)f_j^{(k-1)},1] \leq s_j^{(k-1)}$$

$$= s_j^{(k-1)} \quad \text{otherwise} \quad ...(19)$$

Note that "ζ" is a constraint value of variation

amplitude of the updating of the design variable, and

is set to about 0.3. Further, "$s_j^{(k)}$" is given by

25 $$s_j^{(k)} = [(1/\lambda^{(k-1)})C_j^{(k-1)}]\alpha f_j^{(k-1)} \quad ...(20)$$

Note that "$C_j^{(k)}$" is an amount called a

sensitivity coefficient for the design variable $f_j^{(k)}$ in

23

the second evaluation function L_2 calculated by the processing at step S106.

Further, if the value of the design variable $f_j^{(k)}$ calculated by the expression (19) is less than a predetermined value, it may be forcibly set to 0. the predetermined value is, e.g., about 10^{-3}.

At step S105, the status variable vector $x^{(k)}$ is updated.

The status variable vector $x^{(k)}$ is obtained in process of minimization of the evaluation function by the expression (4). This solution is referred to as a conjugate residual method to be described later.

At step S106, the sensitivity coefficient $C_j^{(k)}$ is calculated by

$$C_j^{(k)} = -(x_j^{(k)})^T(\xi(f_j^{(k)})^{\xi-1}A_j)x_j^{(k)} \quad ...(21)$$

(Sequential Convex Function Approximation Method)

Next, the processing at steps S103 and S104 in a case using the sequential convex function approximate method will be described. In the sequential convex function approximate method, a numerical calculation error can be avoided by scaling of respective components of the design variable vector, however, for the sake of simplification of explanation, no description will be made about the scaling. The details of the sequential convex function approximate method are well known as disclosed in the (reference document 1), (reference document 2) and the like.

24

(Reference document 1) Fujii: "Structural Design Solved by Personal Computer", Maruzen (April 2002)

(Reference document 2) C. Fleury: "CONLIN, an efficient dual optimizer based on convex approximation concepts", Structural Optimization, 1, pp. 81-89 (1989)

At step S103, the Lagrange undetermined constant is updated by the following expression.

$$\lambda^{(k)} = \lambda^{(k-1)} + \Delta\lambda^{(k)} \quad \ldots (22)$$

Note that an initial value $\lambda^{(0)}$ is set to e.g. about 0.01.

"$\Delta\lambda^{(k)}$" is given as a solution of the following equation.

$$\Delta\lambda^{(k)} = 2 \times (1 - W_0/W(f^{(k-1)}))\lambda^{(k-1)} \quad \ldots (23)$$

At step S104, the design variable vector is updated.

$$f_j^{(k)} = (g^{(k)}/\lambda^{(k)})^{1/2} \quad \text{if } 0 < (g^{(k)}/\lambda^{(k)}) < 1$$
$$= 0 \qquad\qquad\qquad \text{if } g^{(k)}/\lambda^{(k)} \leq 0$$
$$= 1 \qquad\qquad\qquad \text{if } 1 \leq g^{(k)}/\lambda^{(k)} \quad \ldots (24)$$

Note that $g^{(k)} = -(f_j^{(k-1)})^2 C_j^{(k-1)} \quad \ldots (25)$

Further, if the value of the design variable $f_j^{(k)}$ calculated by the expression (24) is less than a predetermined value, it may be forcibly set to 0. The predetermined value is, e.g., about 10^{-3}.

The processing at steps S105 and S106 is as described above.

<Calculation and Updating of Status Variable Vector>

(Example of Conjugate Residual Method)

The solution process to calculate the status variable vector $x^{(k)}$ at step S105 is realized by a conjugate residual method, a GCR method, a GCR(k) method, an Orthomin(k) method, a GMRES(k) method, or

5 derivative methods of these methods. Hereinbelow, an example of processing using the conjugate residual method as a representative method will be described with reference to Fig. 4.

At step S301, data in a system to be simulated is

10 read. The data of the system includes an initial value of the status variable vector $x^{(k)}$, the value of the design variable vector $f^{(k)}$, the displacement constraint condition B, and the evaluation function L_1. The program ensures necessary variable areas in the primary

15 storage unit 204 based on the information, and set values. The status variable vector x, the residual vector r, and the search direction vector p are initialized to $X^{(0)}$, $r^{(0)}$ and $p^{(0)}$.

First, the residual vector initial value $r^{(0)}$ is

20 calculated by using the status variable vector initial value $X^{(0)}$ and the nodal force vector b describing a force applied to each node (joint).

$$r^{(0)} = b - Ax^{(0)} \quad ...(26)$$

The search direction vector initial value $p^{(0)}$ is

25 equal to the residual vector initial value $r^{(0)}$.

At step S302, the number of repetitions t is initialized to 1. The number of repetitions t

26

indicates repetitive processing on the above-described status variable solution process. The repetitive processing is terminated when the number of repetitions of processing at the following steps S303 to S307

5 exceeds a set value or when the square of the norm of the residual vector $r^{(1)}$ is less than a predetermined value. Hereinbelow, the value for t-th repetition will be represented as $x^{(t)}$.

At step S303, a status vector update coefficient

10 $\alpha^{(t)}$ is calculated.

$$\alpha^{(t-1)} = (r^{(t-1)}, Ap^{(t-1)})/(Ap^{(t-1)}, Ap^{(t-1)}) \quad \ldots(27)$$

At step S304, the status variable vector x is updated.

$$x^{(t)} = x^{(t-1)} + \alpha^{(t-1)}p^{(t-1)} \quad \ldots(28)$$

15 At step S305, the residual vector $r^{(t)}$ is calculated as follows.

$$r^{(t)} = r^{(t-1)} - \alpha^{(t-1)}Ap^{(t-1)} \quad \ldots(29)$$

At step S306, an update coefficient β of the search direction vector p is calculated.

20 $$\beta^{(t)} = -(Ar^{(t)}, Ap^{(t-1)})/(Ap^{(t-1)}, Ap^{(t-1)}) \quad \ldots(30)$$

At step S307, the search direction vector p is updated.

$$p^{(t)} = r^{(t)} + \beta^{(t-1)}p^{(t-1)} \quad \ldots(31)$$

(Example of Conjugate Gradient Method)

25 Next, an example of processing using the conjugate gradient method as a solution process for calculation of the status variable vector $x^{(k)}$ at step

27

S105 will be described with reference to Fig. 5.

At step S501, data in a system to be simulated is read. The data of the system includes the initial value $x^{(0)}$ of the status variable vector $x^{(k)}$, the

5   initial value $f^{(0)}$ of the design variable vector $f^{(k)}$, the displacement constraint condition B_1, and the evaluation function L_1. The program ensures a necessary variable areas in the primary storage unit 204 based on the information, and set values. The

10   residual vector r and the search direction vector p are initialized to $r^{(0)}$ and $p^{(0)}$.

First, the residual vector initial value $r^{(0)}$ is calculated by using the status variable vector initial value $x^{(0)}$ and the nodal force vector b describing a

15   force applied to each node (joint).

$$r^{(0)} = b - Ax^{(0)} \quad \ldots(32)$$

The search direction vector initial value $p^{(0)}$ is equal to the residual vector initial value $r^{(0)}$.

At step S502, preconditioning is performed.

20   First, among diagonal components of the global stiffness matrix A, a row or column number which becomes 0 is detected. If there is no component which becomes 0, the process proceeds to step S503 without any processing. On the other hand, if there is a

25   component which becomes 0, a component of b (nodal force vector) with a number corresponding to the component is set to 0.

At step S503, the number of repetitions t is initialized to 1. The number of repetitions t indicates repetitive processing on the above-described status variable solution process. The repetitive

5   processing is terminated when the number of repetitions of processing at the following steps S504 to S508 exceeds a set value or when the square of the norm of the residual vector $r^{(t)}$, $(r^{(t)}, r^{(t)})$ is less than a predetermined value. Hereinbelow, the value for t-th

10 repetition will be represented as $x^{(t)}$.

At step S504, a status vector update coefficient $\alpha^{(t)}$ is calculated.

$$\alpha = (r^{(t-1)}, p^{(t-1)}) / (p^{(t-1)}, Ap^{(t-1)}) \quad \ldots (33)$$

At step S505, the status variable vector x is

15 updated.

$$x^{(t)} = x^{(t-1)} + \alpha p^{(t-1)} \quad \ldots (34)$$

At step S506, the residual vector $r^{(t)}$ is calculated as follows.

$$r^{(t)} = b - Ax^{(t-1)} \quad \ldots (35)$$

20 At step S507, an update coefficient β of the search direction vector p is calculated.

$$\beta = (r^{(t)}, r^{(t)}) / (r^{(t-1)}, r^{(t-1)}) \quad \ldots (36)$$

Note that if t = 1 holds, β = 1 holds.

At step S508, the search direction vector p is

25 updated.

$$p^{(t)} = r^{(t)} + \beta p^{(t-1)} \quad \ldots (37)$$

The conjugate residual method, the conjugate

gradient method and their various derivative methods

are well-known as disclosed in (Reference Document 3),

(Reference Document 4), (Reference Document 5),

(Reference Document 6), (Reference Document 7) and the

5   like. It has been shown that these methods attain

convergence in a stable manner even in a case where a

coefficient matrix A is singular.

(Reference Document 3) Mori, Sugihara and Murota:

"Linear Computation", Iwanami Kohza Applied Mathematics,

10   Iawanami-Shoten (1994)

(Reference Document 4) Hayami: "On the convergence of

GCR(k) on singular system", Kyoto University

Mathematical Analysis Research Laboratory, transcript

of lectures and studies 1265 (2002)

15   (Reference Document 5) Abe, Ogata, Sugihara, Zhang,

Mitsui: "Convergence of CR on simultaneous linear

equations having singular coefficient matrix", Japan

Journal of Industrial and Applied Mathematics, Vol. 9,

No. 1, pp. 1-13 (1999)

20   (Reference Document 6) K.Hayami: "On the Behavior of

the Conjugate Residual Method for Singular Systems",

NII Technical Report, NII-2001-002E (2002)

(Reference Document 7) S-L. Zhang, Y. Oyanagi, M.

Sugihara: "Necessary and sufficient conditions for the

25   convergence of Orthomin(k) on singular and inconsistent

systems", Numerische Mathemarik, 87, pp. 391-405 (2000)

(Particular Example of Structure Optimal Designing of

Present Embodiment)

In this example, the present embodiment is applied to automatic designing of optimal shape of a cantilever which receives a load applied to an

5 arbitrary position. For the sake of simplification of explanation, the designing is limited to a plan strain problem.

As shown in Fig. 6, a design area where structural members exist is a rectangle 402 divided by

10 vertical n_y and lateral n_x at equal intervals in accordance with the finite element method. Each divided partial area is called a cell. The cells are numbered such that a bottom left cell is (1, 1) and a top right cell is (n_y, n_x).

15 Similarly, each grid point is called a node. The nodes are numbered such that a bottom left node is (1,1) and a top right node is (n_y+1, n_x+1).

In Fig. 6, numeral 401 denotes a support member; and 403, a load vector.

20 A characteristic function value f(j,k) corresponds to a cell (j,k). The characteristic function value is a variable having a positive real value ranging from 0 to 1, indicating the rate of existence of structural member in the cell (j,k). The

25 characteristic function value is an element of the design variable vector f of the present embodiment.

$$f = (f(1,1),f(1,2), \ldots, f(n_y,n_x))^T \quad \ldots(38)$$

31

Similarly, a lateral displacement u(j,k) and a vertical displacement v(j,k) correspond to the node (j,k). They are real numbers having an arbitrary value, and are elements of the status variable vector x of the

5 present embodiment.

$$X = (u(1,1), v(1,1), u(1,2), v(1,2), \ldots, u(n_y+1,n_x+1), v(n_y+1,n_x+1))^T \ldots (39)$$

Fig. 7 shows the result of computation. In Fig. 7, a black area indicates an area where the structural

10 member exists. In the present example, the vertical-to-lateral aspect ratio of structural members in the design area is 2/1. The analytical solution is a combination of ±45° beams with respect to a horizontal direction. The result of computation in Fig. 7

15 corresponds with the analytical solution.

In the present embodiment, the apparatus has been described as one system where the respective units are connected to the bus line 207. However, the system may be realized as plural devices by connecting the

20 respective elements via a network or the like. Otherwise, plural general computers may be connected for execution of multiple-processing or distributed processing in parallel.

Further, the present invention includes a program

25 to realize the above-described structure optimal designing method and a storage medium holding the program in a computer-readable manner.

The present invention is not limited to the above embodiments and various changes and modifications can be made within the spirit and scope of the present invention. Therefore, to appraise the public of the

5　scope of the present invention, the following claims are made.